



SEPARATORY CYKLONOWE WODY SERII CKL

Ciśnienie pracy	16 bar
Przepływy	120 – 2850 Nm³/h
Przyłącza	3/8" – 3"
Temp. pracy	1,5 – 65°C
Kolor standardowy	RAL 9005
Skuteczność	> 98%



TECHNICAL DATA											
Model	Pipe size	Max. oper. pressure	Flow rate at 7 bar(g), 20 °C		Temperature oper. range		Dimensions [mm]				Mass
	inch	bar/psi	Nm ³ /h	SCFM	°C	°F	A	B	C	D	kg
CKL 005 B	3/8"	16/232	60	35	1,5 - 65	35 - 149	192	88	25	60	0,6
CKL 007 B	1/2"	16/232	78	46	1,5 - 65	35 - 149	192	88	25	60	0,6
CKL 010 B	3/4"	16/232	120	70	1,5 - 65	35 - 149	264	88	25	80	0,7
CKL 018 B	1"	16/232	198	116	1,5 - 65	35 - 149	264	125	39	100	1,9
CKL 047 B	1 1/2"	16/232	510	300	1,5 - 65	35 - 149	464	125	39	140	1,9
CKL 094 B	2"	16/232	1000	588	1,5 - 65	35 - 149	694	163	50	520	5,7
CKL 150 B	2 1/2"	16/232	1500	882	1,5 - 65	35 - 149	694	163	50	520	7,6
CKL 200 55"	3"	16/232	2160	1270	1,5 - 65	35 - 149	801	242	60	630	14,1

* wartości podane dla ciśnienia 7 bar, dla ciśnienia 10 bar mnożnik x1,38

OMEGA AIR d.o.o. Ljubljana
 Cesta Dolomitskega odreda 10
 SI-1000 Ljubljana, Slovenia
 Tel.: +386 (0)1 200 68 00
 Fax.: +386 (0)1 200 68 50
 E-mail: info@omega-air.si
www.omega-air.si

Dystrybutor w Polsce:
 Medpipe Sp. z o.o.
 Niemierzyńska 17A
 71-441 Szczecin
www.medpipe.pl